

Edge Banding - PUR Hot Melt

Edge banding is one of the most used operation within furniture industry. Furthermore, production lines and materials used are constantly changing in order to fulfill new design requirements and improve final customer experience. Waterproofing, heat resistance and durability requirements are always stricter. Durante Vivan can provide you a wide range of polyurethane hot melts, that can fit all your needs.



ADVANTAGES

- Invisible glue line
- Heat resistance up to 150°C
- Steam and water resistance
- Easy to use

TECHNICAL DATA

Product name	Description	Fields of application
Duditerm PU 152/5	Invisible glue line	Unfilled product. Suitable for roller and slot nozzle application. Straight edges.
Duditerm PU 145	Invisible glue line	Suitable for roller and slot nozzle application. Suitable for straight edges.
Duditerm PU 130/1	All seasons product	Suitable for roller and slot nozzle application. Suitable for straight edges. Also suitable for softforming and BAZ.
Duditerm PU 127/5	Suitable for fast lines	Suitable for roller and slot nozzle application. Suitable for straight edges. Also suitable for softforming and BAZ.
Duditerm PU 157LM	<i>Low monomer</i>	Suitable for roller and slot nozzle application. Suitable for straight edges.

PACKAGING AND STORAGE

Our polyurethane hot melts are available in 2 kg, 20 kg and 200 kg packaging sizes within sealed aluminium bag. Shelf life 12 months in original sealed containers under dry and cool conditions.